

DEFENDER S3 CI WR AN

TO159D

CE UNI EN ISO 20345:2012 S3 CI WR AN SRC

High shoe, WRU back leather thickness 1,8 □ 2,0 mm.
Highly perspiring and abrasion-resistant fabric lining. Soft Windtex® water resistant membrane lining, with very good perspiration and abrasion resistance.
Shoe with refracting fabric insert.
Soft, lined and padded tongue.

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE STABILE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

ANTITORSION insert in the sole to assure stability on uneven ground

INSOLE 5000, three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial

CI insulated surface against cold -17°C

WR water resistant shoe

AN ankle protection

THIS PRODUCT COMPLIES WITH THE REQUIREMENTS OF THE STANDARD ASTM F2413-18:

- Impact resistant footwear (I)
- Compression resistant footwear (C)
- Puncture Resistant Footwear (PR)

Size 39-47 Shoe weight Sz 42 gr. 710




CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS



SOLE



Stabile is the comfortable alternative to the classic and "heavy" shoe for building sector. This sole is highly performing with specific dowels, with dimensions and shapes to assure the maximum stability, with self-cleaning drainage channels to assure a perfect cleaning and with a soft compound to isolate the foot to the continuous shocks. Line studied with a lot of attention to the technology of uppers and lightness of the materials.

ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS			
SRC			
ISO 20345:2012			
SRA	HELD >= 0,20	0,40	0,40
CONTRIC +	FLAD >= 0,20	0,44	0,44
SMB	HELD >= 0,20	0,20	0,20
2000 +	FLAD >= 0,20	0,20	0,20

PLUS



WINDTEX®

Windtex® is an innovative membrane that blocks wind and water, by guaranteeing at the same time a homogeneous transpiration of the foot. The degree of transpiration of Windtex® together with windproof property, allow the maintenance of microclimate of the shoe. This membrane, with technology Aegis®, builds and antimicrobial barrier against unpleasant odors, fungi and other microorganisms.



ANTI TORSION

The usage of the anti-torsion shank is finalized to give to the shoe extreme stability on every ground. Mostly indicated for the building sector, where the risks caused by uneven and wet grounds are higher, this technology is very useful for people working on ladders (painters, windows' cleaners, bricklayers) as it increases the stability in the centrla part of the plant, the mostly standed area on the ladder. It limits the heel stress and helps plant arch and ankle.