

# IRON RM S3

AC068DRM

CE UNI EN ISO 20345:2012 S3 M SRC

High shoe, WRU back leather thickness 1,8-2,0 mm.

Perspiring and abrasion resistant fabric lining

Shoe with refracting insert.

Soft, lined and padded tongue.

Shoe with fast device.

**TOECAP 200J** polymeric **composite non-thermic** according to EN 12568

**MIDSOLE flexible antiperforation composite fabric** according to EN 12568

**SOLE ACTION** bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

**INSOLE 4000**, removable, anatomic, absorbing, antistatic and perspiring

**M** metatarsal protection

**Size 37-47 Shoe weight Sz 42 gr. 650**



## CERTIFICATIONS



## TECHNOLOGIES AND MATERIALS



## SECTORS



FARMING AND MINING



BUILDING AND HEAVY INDUSTRY

## SOLE



Action is a shoe studied for external jobs, with soft lines making it very light and comfortable.

## PLUS

## ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS

SRC		SRC	
SHOES	HEEL	SOLE	SCORE
SHOES	HEEL	SOLE	SCORE
SHOES	HEEL	SOLE	SCORE