

# OXFORD S3

KU068D

CE UNI EN ISO 20345:2012 S3 SRC

High shoe, back WRU leather thickness 1,8-2,0 mm.  
Perspiring and abrasion resistant fabric lining.  
Shoes with refracting fabric insert.  
Soft, lined and padded tongue.

The shoe satisfies the requirements of slipping resistance on inclined roofs according to **UNI 11583:2015 TOECAP 200J** polymeric **composite non-thermic** according to EN 12568  
**MIDSOLE flexible antiperforation composite fabric** according to EN 12568  
**SOLE KUBE** bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC INSOLE 4000**, removable, anatomic, absorbing, antistatic and perspiring

**Size 35-49 Shoe weight Sz 42 gr. 550**



## CERTIFICATIONS



## TECHNOLOGIES AND MATERIALS



## SECTORS



## SOLE



In order to avoid the high number of accidents caused by slipping danger, Giasco realized an excellent anti-slipping product. This sole is called Kube, a young and sporty styled shoe equipped with a special gripping compound and specific cubic dowels with inverted profile in the outsole. With thanks to these special characteristics Kube obtained the maximum certification against slipping: jobs on inclined roofs (UNI 11583:2015).

## PLUS

## ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS			
<b>SRC</b>			
ANTI-SLIPPING TEST			
SRX	HEEL=0,630	0,40	
CONTRAC +	PLATEFORM=0,630	0,40	
SRB	HEEL=0,630	0,30	
SRB +	PLATEFORM=0,630	0,30	